


ode : .....

# **RECESSED LED STAIR LIGHT & WALL LIGHT**


PROJECT DATA	Assigned c
Project :	Location :
Approved by :	Date :



## MODEL: MS1QR0102-1x3W

## Approval and marking





## Product color



## **Technical information**

• Model	: MS1QR0102-1x3W
• Led chip	: LED COB OSRAM
Rated power	: 1x3W
• Luminous flux	: 80lm (cool white), 72lm (warm white)
<ul> <li>Luminous efficacy</li> </ul>	: 26.7lm/W (cool white), 24lm/W (cool white)
<ul> <li>Input voltage</li> </ul>	: DC24V/AC120/240V 50/60Hz
Color temperature	: 2700K/3000K/4000K/5700K/6500K
• Beam angle	: Asymmetric
Control method	: On/off, Triac, PWM, 1-10V, Dali
Protection grade	: IP65
• IK rating	: IK10
Operating temperature	:-20°C~40°C
Product life	: 35000 hours

We reserve the right to make technical and design changes.

# Introduction

Recessed LED stair light & wall is the recessed mounting luminaire for indoor/outdoor use. The manufacture process is extremely strict, high quality output with CE, ROHS certified. Its excellent light brings comfort and good experience to the users.

## Feature

• Front cover & housing 12# die-casting aluminum anti-corrosion powder coating T=20-25µm, adhesion of ISO class 1/ ASTM class 4B high temperature painting.

• Light window glass.

• Power cable outside of luminaire H05RN-F 2×1.0mm<sup>2</sup>, L=0.3m(DC24V), H05RN-F 3×1.0mm<sup>2</sup>,

- L=0.3m (AC120/240V).
- · LED driver constant voltage input, constant current output.
- Mounting sleeve PC/ABS alloys.
- Warranty 3 year.

#### Application area

Applied to stairs, way, facade of building, hotel, resort and etc.

## Mounting type

• Recessed mounting.


## Dimension: (mm)





Option 2: mounting sleeve 100#

## Photometric data





## THIEN MINH MECHANICAL - ELECTRIC JSC

Head office: MESTAR Building, No. 98/11 Ung Van Khiem Street, Ward 25, Binh Thanh District, Ho Chi Minh City, Vietnam Tel: (84) 28.3899 4790 - Email: mestar@mestar.vn - Web: www.mestar.vn