

MINI UPPER 1 - LED IN-GROUND LUMINAIRE

PROJECT DATA	Assigned code:
Project:	Location:
Approved by:	Date :



Introduction

MINI UPPER 1 is the beautiful way to add some attractive lighting to your outdoor living space. With impression light outputs, they are perfect for decking and ground lights.

Features

- · Front cover: hard chrome plated stainless steel.
- Housing: aluminum anodized finish.
- Light window: tempered step glass. T=2mm.
- Gasket: silicone rubber molding shaped seal.
- Recessed sleeve material: PC/ABS alloys.
- Optical lens with multi beam angle option and efficiency ≥ 85%.
- CCT: 2700K/3000K/4000K/5700K/6500K.
- DC24V input voltage.
- IP classification: IP67.

Applications areas

• Stair step indicator, porch wall foot, roads, squares, sidewalks, garden, patio, yard, lawn, pool deck, pathway, driveway, walkway, bridges marker, etc.

Mounting type

• Ground recessed, floor recessed.

Approvals and markings






IP67

IK02

Feature



Beam angle



Lens




Product color



Dimension: (mm)





Technical information

• Model	: MS2BPR0134-0.5W	
• Led brand	: OSRAM	
• Led quantity	:1pc	
Rated power	: 0.5W	
• Luminous flux	: 22.95lm ±10%	
Input voltage	: DC24V	
Color temperature	: 2700K/ 3000K/ 4000K/ 5700K/ 6500K	
• Beam angle	: 10º/15º/20º/30º	
• Control method	: On/off	
Protection grade	: IP67	
Ambient temperature	: -20°C~40°C	
Ambient humidity	: 10%~90%	
• Product life	: 35.000hrs	



We reserve the right to make technical and design changes.






MINI UPPER 1 - LED IN-GROUND LUMINAIRE

PROJECT DATA	Assigned code:
Project:	Location:
Approved by	Date:

Sleeve (Included)













Recessed Sleeve 113# unable to put water-stopper and connector

Waterproof solution



■ Water-Stopper (Included)

The luminaire will generate high temperature when used, which will generate negative pressure when the power is turned off also brings water vapor into the luminaire. That's why the device is required to block the entry of water vapor.

B IP67 Jiffy quick plug/socket connector (Option)

To prevent water vapor into luminaire via wire which had been cut, the air contains lots of steams when raining, spray or in humid environment, the luminaire will generate high temperature when used, which will generate negative pressure when the power is turned off also brings water vapor into the luminaire.

Connection Accessories



Connector 3 pin - IP68

MA-M684-03



T Connector 3 pin - IP68

MA-M685T-03



Y Connector - IP68

MA-M685Y-03



Juntion box 3 holes - IP68

MA-M686-03

We reserve the right to make technical and design changes.

