



FLOODLIGHTS AND PROJECTORS





Introduction

COMPACT 7 is surface architectural floodlight family, adopt isolated two bodies design could have the separate heat dissipation structure to fully ensure the stability and long lifespan of LED light. With multiway rotate function of round support, spike, pole or U-bracket mounting are available to meet various occasions demands for outdoor projects.

Features

- · High pressure die-casting aluminum housing.
- · High strength toughened glass.
- Surface finish with fluorine carbon spraying ensuring high corrosion resistance, resist the impact and friction.
- LED module: high-power LEDs on metal-core PCB
- High-efficiency PMMA lens with various beam angle option.
- Adopt American CREE original LED light source, high flux output, excellent consistency of color.
- Constant current AC100-240V driver with On/Off, DALi, 0-10V control method or DC24V, DC36V input voltage with DMX512, RDM control method.
- Single color with various temperature option: 2700K/3000K/4000K/5000K/6000K.
- Dynamic color with RGB option have gray level reach 65,536 degree equally make the light result is more beautiful.
- · Powerful DMX512 interface adopt high reliable bus connect, all has the function of automatic addressing.

Applications areas

· Facade of outdoor buildings, billboards, sculptures etc.

Mounting type

• Surface mounting, spike or tile clips mounting etc.

Approvals and markings







IP66

IK08

Feature














Dimension (mm):



MS3HC01102F (Flange base)





Beam angle











Color temperature

Single

Dynamic

- · 3000K
- 4000K
- 5000k
- 6000K

Product colour













Date: 22-03-2021



We reserve the right to make technical and design changes.






Head office: MESTAR Building, No. 98/11 Ung Van Khiem Street, Ward 25, Binh Thanh District, Ho Chi Minh City, Vietnam. Tel: (84) 28.3899 4790 - Email: mestar@mestar.vn - Web: www.mestar.vn Ha Noi Office: TT4.18, Xuan Phuong Tasco Urban Area, Xuan Phuong Ward, Nam Tu Liem District, Hanoi City, Vietnam. Tel: (84) 24.3222 2411






Variants








MS3HC01102M (Ø48-pole mounting part)





MS3HC01102S (Inclined cover)
















We reserve the right to make technical and design changes.

Date: 22-03-2021








Specification

Model	MS3HC01102UD-105W	MS3HC01102UC-86W	MS3HC01102UB-60W	MS3HC01102UC-50W
Led brand	CREE XP-G3	CREE	CREE	CREE
Led quantity	36pcs	36pcs	36pcs	24pcs
Rated power	105W	86W	60W	50W
Lumen	6825lm (±10%)	3440lm/5590lm (±10%)	2400lm/3900lm (±10%)	2000lm/2350lm (±10%)
Input voltage	AC100-240V	DC24V/AC100-240V	DC24V/AC100-240V	DC36V/AC100-240V
Frequency range	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Color temperature	Single	RGB/Single	RGB/Single	RGB/Single
Beam angle	5º 8º 12.5º 20º 30º 45º 60º 15x30º 10x60º			
Control method	On/Off	On/Off, DALi, 0-10V	DMX512, RDM	DMX512, RDM
Protection grade	IP66	IP66	IP66	IP66
Ambient temperature	-25°C~50°C	-25°C~50°C	-25°C~50°C	-25°C~50°C
Ambient humidity	10%~90%	10%~90%	10%~90%	10%~90%
Product life	50000H	50000H	50000H	50000H

Model	MS3HC01102FD-105W	MS3HC01102FC-86W	MS3HC01102FB-60W	MS3HC01102FC-50W	
Led brand	CREE	CREE	CREE	CREE	
Led quantity	36pcs	36pcs	36pcs	24pcs	
Rated power	105W	86W	60W	50W	
Lumen	6825lm (±10%)	5590lm (±10%)	3900lm (±10%)	2350lm (±10%)	
Input voltage	AC100-240V	AC100-240V	AC100-240V	AC100-240V	
Frequency range	50/60Hz	50/60Hz	50/60Hz	50/60Hz	
Color temperature	Single	Single	Single	Single	
Beam angle	5° 8° 12.5° 20° 30° 45° 60° 15x30° 10x60°				
Control method	On/Off	On/Off	On/Off	On/Off	
Protection grade	IP66	IP66	IP66	IP66	
Ambient temperature	-25°C~50°C	-25°C~50°C	-25°C~50°C	-25°C~50°C	
Ambient humidity	10%~90%	10%~90%	10%~90%	10%~90%	
Product life	50000H	50000H	50000H	50000H	

Typical order example



We reserve the right to make technical and design changes.

Date: 22-03-2021





Accessories



Anti-glare shield

MA-1102-AGS



Honeycomb grill

MA-1102-HGR

MS3HC01102UD-105W	•	•
MS3HC01102UC-86W	•	•
MS3HC01102UB-60W	•	•
MS3HC01102UC-50W	•	•
MS3HC01102FD-105W	•	•
MS3HC01102FC-86W	•	•
MS3HC01102FB-60W	•	•
MS3HC01102FC-50W	•	•

Connection Accessories



Connector 3 pin - IP68

MA-M684-03



T Connector 3 pin - IP68

MA-M685T-03



Y Connector - IP68

MA-M685Y-03



Juntion box 3 holes - IP68

MA-M686-03

We reserve the right to make technical and design changes.