



# **FLOODLIGHTS AND PROJECTORS**

Date: 12-03-2021





#### Introduction

MAXI 4 is the super high architectural floodlight series, adopt isolated two-body design to separated dissipation for fully ensuring the stability and long lifespan of LED light. Special 2-module design with flexible arm for angle adjustment. Multi-way rotate function of special U-shaped bracket to meet various occasions demands for outdoor projects.

#### Features

- · High pressure die-casting aluminum housing.
- · High strength toughened glass.
- Inclined cover and honey comb accessories for anti-glare options.
- Surface finish with fluorine carbon spraying ensuring high corrosion resistance, resist the impact and friction.
- LED module: High-Power LEDs on metal-core PCB.
- High-efficiency PMMA lens with various beam angle option.
- Adopt American CREE original LED light source, high flux output, excellent consistency of color, LUMILEDS light source optional.
- $\bullet \ \text{Input power supply AC100-305V driver for both On/Off control method and DMX512/ RDM control method.}\\$
- $\bullet \ Single \ color \ with \ various \ temperature \ option: 2700 \ K/3000 \ K/4000 \ K/5000 \ K/6000 \ K.$

900 750

- $\bullet \, \text{Dynamic color with RGBW, RGBA option have gray level reach 65,536 degree equally make the light result is more beautiful.} \\$
- Powerful DMX512 interface adopt high reliable bus connect, all has the function of automatic addressing.
   Remote Device Management (RDM) is an enhancement of DMX, allowing full bi-directional control and communication for simple, convenient commissioning.

### Applications areas

· Facade of outdoor buildings, billboards, area, port etc.

Dimension (mm):

#### Mounting type

Surface mounting.

## Approvals and markings





IP66

MODEL: MS3HMA1272U

IK08

### Feature













#### Beam angle



## MS3HMA1272UE/D/F (u-shaped bracket)





## Color temperature

• 2700K

Dynamic
• RGBW
• RGBA

• 3000K

• RGB/

• 4000K

• 6000K

#### Product colour



We reserve the right to make technical and design changes.

#### Date: 12-03-2021




### THIEN MINH MECHANICAL - ELECTRIC JSC





#### Variants



MS3HMA1272SE/D/F (u-shaped bracket with inlined cover)








## Specification

Model	MS3HMA1272UD-600W	MS3HMA1272UC-420W	MS3HMA1272UF-720W
Led brand	CREE/LUMILEDS	CREE/LUMILEDS	CREE RGBW 4 in 1
Led quantity	180pcs	180pcs (48R 48G 48B 36W)	80pcs
Rated power	600W	420W	720W
Lumen (RGBW/RGBA)	/	16800lm (±10%)	28800lm (±10%)
Lumen (Single)	39000lm (±10%)	27300lm (±10%)	/
Input voltage	AC100-305V	AC100-305V	AC100-305V
Frequency range	50/60Hz	50/60Hz	50/60Hz
Color	Single	RGBW/RGBA/Single	RGBW
Beam angle	2.6° 3.5° 6° 12° 20° 30° 45° 60° 5x20° 10x70°		8º 25º 10x45º
Control method	On/Off	DMX512, RDM, On/Off	DMX512, RDM
Protection grade	IP66	IP66	IP66
Ambient temperature	-25°C~50°C	-25°C~50°C	-25°C~50°C
Ambient humidity	10%~90%	10%~90%	10%~90%
Product life	80000H	80000H	80000H

## Typical order example



We reserve the right to make technical and design changes.

Date: 12-03-2021





Head office: MESTAR Building, No. 98/11 Ung Van Khiem Street, Ward 25, Binh Thanh District, Ho Chi Minh City, Vietnam.
Tel: (84) 28.3899 4790 - Email: mestar@mestar.vn - Web: www.mestar.vn

Ha Noi Office: TT4.18, Xuan Phuong Tasco Urban Area, Xuan Phuong Ward, Nam Tu Liem District, Hanoi City, Vietnam. Tel: (84) 24.3222 2411



#### Accessories





Inclined cover

MA-1272-AGS

Honeycomb grill

MA-1272-HGR

MS3HMA1272UD-600W	•	•
MS3HMA1272UC-420W	•	•

MS3HMA1272UF-720W •

#### **Connection Accessories**



Connector 3 pin - IP68

MA-M684-03



T Connector 3 pin - IP68

MA-M685T-03



Y Connector - IP68

MA-M685Y-03



Juntion box 3 holes - IP68

MA-M686-03