

STARLUX 4-FLOODLIGHTS AND PROJECTORS

PROJECT DATA	Assigned code:
Project:	Location:
Approved by :	Date :



MODEL: MS3HST1135UE-75W

Introduction

STARLUX 4 is modern architectural floodlight series, adopt elegant and distinctive design with long-lasting structure to fully ensure the stability and lifespan of LEDs. With multi-way rotate function of round support, spike, pole or tree mounting are available to meet various occasions demands for outdoor projects.

Features

- · High pressure die-casting aluminum housing.
- · High strength toughened glass.
- Surface finish with fluorine carbon spraying ensuring high corrosion resistance, resist the impact and friction.
- LED module: high-power LEDs on metal-core PCB.
- High-efficiency PMMA lens with various beam angle option.
- Adopt American CREE original LED light source, high flux output, excellent consistency of color.
- Constant current AC100-305V input driver with On/Off control method.
- Single color with various temperature option: 2700K/3000K/4000K/5000K/6000K.

Applications areas:

• Facade of outdoor buildings, billboards, sculptures, garden etc

Installation:

- Surface mounting, spike, pole, tree mounting etc.
- Pole installation with single side or double sides mount with different type of arm for multi-purpose application.

Approvals and markings







IP66

IK08


Dimension: (mm)







Beam angle



Product color



Technical information

• Model	: MS3HST1135UE-75W
• Material	: Die-casting aluminium
• Lamp	: CREE XP-L
• Power	: 75W
• Luminous flux	: 4875lm ±10%
• CCT/Ra	: 2700K/ 3000K/ 4000K/ 5000K/ 6000K/ Ra>80
• Efficacy	: 65lm/w
Beam angle	: 2.6°/ 3.5°/ 6°/ 12°/ 20°/ 30°/ 45°/ 60°/ 10x70°/ 5x20°
• Control method	: On/off
• Product color	: Pearl dark grey
Ambient temperature	: -25°C~50°C
• Input voltage	: 100-305V~ 50/60Hz
Product life	: 50.000hrs

Photometric Data



We reserve the right to make technical and design changes.

