

# STARLUX 2-FLOODLIGHTS AND PROJECTORS

PROJECT DATA	Assigned code:
Project:	Location:
Approved by :	Date :



MODEL: MS3HST1137UF-30W

## Introduction

STARLUX 2 is modern architectural floodlight series, adopt elegant and distinctive design with long-lasting structure to fully ensure the stability and lifespan of LEDs. With multi-way rotate function of round support, spike, pole or tree mounting are available to meet various occasions demands for outdoor projects.

### **Features**

- High pressure die-casting aluminum housing.
- High strength toughened glass.
- Surface finish with fluorine carbon spraying ensuring high corrosion resistance, resist the impact and friction.
- LED module: high-power LEDs on metal-core PCB.
- High-efficiency PMMA lens with various beam angle option.
- Adopt American CREE original LED light source, high flux output, excellent consistency of color.
- Dynamic color with RGBW option has gray level reach 65,536 degree equally make the light result is more
- Powerful DMX512 interface adopt high reliable bus connect, all has the function of automatic addressing.

**Applications areas:** Facade of outdoor buildings, billboards, sculptures, garden etc.

Installation: Surface mounting, spike, pole, tree mounting etc.

## Approvals and markings





IP66

**IK08** 



Beam angle











### Dimension: (mm)








## Technical information

• Model	: MS3HST1137UF-30W
Material	: Die-casting aluminium
• Lamp	: CREE RGBW 4 in 1
• Power	: 30W
• Luminous flux	: 1200lm ±10%
• CCT/Ra	: RGBW
• Efficacy	: 40lm/w
Beam angle	: 15°/ 20°/ 30°/ 15x60°
• Control method	: DMX512
• Product color	: Pearl dark grey
Ambient temperature	: -25°C~50°C
Input voltage	: DC24V/ 100-264V~ 50/60Hz
Product life	: 50.000hrs

## Photometric Data



We reserve the right to make technical and design changes.

