

## WALL MOUNTING LANDSCAPE LAMP



# WALL MOUNTING LANDSCAPE LAMP



## Introduction

Wall mounting landscape lamp is the surface mounting luminaire for indoor/outdoor use. The manufacture process is extremely strict, high quality output with CE, ROHS certified. Its excellent light brings comfort and good experience to the users.

## Feature

- Housing and front cover 12# aluminum with anti-corrosion powder coated, T=60-80µm. Adhesion of ISO class 1/ASTM class 4B.
- Light window UVstop & fireproof PC T=6mm.
- Gasket tooling shaped seal.
- LED driver main voltage AC100V-240V driver inside builded.
- Power cable outside of luminaires H05RN-F 2×1.0mm<sup>2</sup> L=0.3m (DC24V), H05RN-F 3×1.0mm<sup>2</sup> L=0.3m (AC120/240V).
- Warranty 3 years.

## Application area

- Applied to facade of building, hotel, resort and etc.

## Mounting type

- Surface mounting.


## Approval and marking



## Feature



## Dimension (mm):



## Beam angle



## Color temperature

### Single


2700K 3000K 4000K 5700K 6500K

## Product color





# WALL MOUNTING LANDSCAPE LAMP

## Variant



MS7AB0237-2x3W



MS7AC0237-2x3W

## Specification

Model	MS7AB0237-2x3W	MS7AC0237-2x3W
Led brand	LED COB NICHIA	LED COB NICHIA
Rated power	2x3W	2x3W
Luminous flux	2x210lm	98lm (Up), 195lm (Down)
Luminous efficacy	2x70lm/W	32.7lm/W (Up), 65lm/W (Down)
Input voltage	DC24V/AC120/240V 50/60Hz	DC24V/AC120/240V 50/60Hz
Color temperature	2700K/3000K/4000K/5700K/6500K	2700K/3000K/4000K/5700K/6500K
Beam angle	75°	Up 6° down 75°
Control method	On/off, Triac, PWM, 1-10V, Dali	On/off, Triac, PWM, 1-10V, Dali
Protection grade	IP65	IP65
IK rating	IK06	IK06
Operating temperature	-20°C~40°C	-20°C~40°C
Product life	35000 hours	35000 hours

## Typical order example

