

SHINING - LED POST TOP LIGHT



Introduction

Shining is the surface luminaire for outdoor use. The manufacture process is extremely strict, high quality output with CE certified. Its excellent light brings comfort and good experience to the users.

Feature

- Housing material is die-casting aluminum with anti-corrosion powder coating finish.
- Housing with high anti-corrosion paint in the near-sea environment (optional).
- Supper white toughened glass.
- Double photometric diffuser technology.
- Use chip LED CREE high quality.
- Input voltage AC120-240V 50/60Hz with On/off control method.
- Color temperature: 3000K/4000K/5700K/6500K.
- Beam angle with 3 options: TYPE I/TYPEII/TYPE III.
- Warranty 3 years.

Application area

- Applied to park, pathway, garden, community area, etc.

Mounting type

- Surface mounting.


Approval and marking



Product color



Dimension: (mm)



Feature



Beam angle



Technical information

• Model	: MS8SSN6142-55W
• Led brand	: LED CREE
• Rated power	: 55W
• Luminous flux	: 6765lm
• Luminous efficacy	: 123lm/W
• Input voltage	: AC120-240V 50/60Hz
• Color temperature	: 3000K/4000K/5700/6500K
• Beam angle	: TYPE I/TYPE II/TYPE III
• Control method	: On/off
• Protection grade	: IP65
• Operating temperature	: -40°C~50°C
• Product life	: >50000 hours



We reserve the right to make technical and design changes.

THIEN MINH MECHANICAL - ELECTRIC JSC

Head office: MESTAR Building, No. 98/11 Ung Van Khiem Street, Ward 25, Binh Thanh District, Ho Chi Minh City, Vietnam

Tel: (84) 28.3899 4790 - Email: mestar@mestar.vn - Web: www.mestar.vn

